



Popoto M2000

Product Overview:

The Popoto M2000 is an advanced underwater acoustic modem which delivers superb performance, unique features, and flexible interfacing, allowing for use in nearly any application. Featuring a machined aluminum casing which can withstand depths of up to 2000 meters and a transmitter capable of transmitting at up to 100W, the M2000 is both versatile and robust.

Features:

- Multiple modulation schemes from 80 BPS to 10240 BPS
- Python API for on-board user programming
- MATLAB API for data analysis
- Acoustic ranging (Accurate to <0.3m)
- High-capacity data logging (SD card or optional SATA drive)
- Baseband and passband waveform playback and recording
- JANUS (NATO ANEP-87) compliant version available
- Single Sideband Analog Voice



\$6600 USD*

*includes 77wh Li-Ion battery, charger, and 1m lab cable





Data Transfer	
Data Rates	80 bps with Frequency Hopping FSK 10240, 5120, 2560, 1280, 640 bps with PSK
Storage	Up to 64 GB on uSD Expandable with optional SATA Drive
Range	1-8 km depending on conditions and modulation scheme selected.
Frequencies	22-35 KHz selectable
Transducer Type	20-30 KHz Omnidirectional
Voice Communications	
Voice Features Included	Single Sideband Voice Adaptive Squelch and Vox Noise Cancellation
Power	
Operating Voltage Range	8.5-36V
Power Draw	GPIO Enabled Sleep: < 10uW Acoustic Wake Up Deep Sleep: <45 mW Acoustic Wake Up Sleep: 150 mW Active Receive: 1.5 W
Transmit Power	100 W
Battery	1 to 4 x 77Wh 22.2V Li-Ion
Interface	
Data Connections	Ethernet, RS-422, RS-232
External Interface Connections	SPI Bus, I2C Bus, GPIO, Analog
APIs	Python, C++, MATLAB, Rust (Coming Soon)
Hardware	
Size	430mm x 100mm x 100mm
Weight	Dry: 3.6 to 4.5Kg In Sea Water: 0.5 to 1.4Kg
Depth Rating	2000m
Export Classifications	5A991 Controlled for anti-terrorism only

